## **LISTING OF CLAIMS:**

- 1.-2. (Cancelled).
- 3. (Currently Amended) The A timepiece according to claim 2, wherein comprising:

a dial having a dial cover and a time display section on an inner peripheral side thereof;

an hour hand being mounted on the time display section and having an hour hand rotating shaft disposed at a position different from the center position of the time display section;

a minute hand being mounted on the time display section and having a minute hand rotating shaft disposed at a position different from the center position of the time display section and concentric with the hour hand rotating shaft, the hour hand rotating shaft and the minute hand rotating shaft being disposed at a position eccentric from the center position of the time display section in a 6:00 direction;

a pointer being mounted at a position eccentric from the center of the time display section and different from the hour hand rotating shaft and minute hand rotating shaft on the time display section and having a pointer rotating shaft, a dimension A from the pointer rotating shaft to a tip of the pointer being greater than a dimension B from the minute hand rotating shaft to a tip of the minute hand, the pointer rotating shaft being disposed at a position away from the hour hand rotating shaft by a distance less than the dimension A and

greater than the dimension B, the pointer rotating shaft being disposed on the opposite side of the center position of the time display section from the hour hand and minute hand rotating shafts, and the pointer rotating shaft [[is]] being disposed at a position eccentric from the center position of the time display section in a 12:00 direction[[,]]; and

a movement being configured to drive the hour hand, the minute hand, and the pointer
the hour hand rotating shaft and the minute hand rotating shaft are disposed at a
position eccentric from the center position of the time display section in a 6:00 direction.

4. (Previously Presented) The timepiece according to claim 3, further comprising,

a case to accommodate the dial, the hour hand, the minute hand, the pointer, and the movement, and

a wrist mounting strap connected to the case.

5. (Currently Amended) The A timepiece according to claim 1, further comprising[[,]]:

a dial having a dial cover and a time display section on an inner peripheral side thereof;

an hour hand being mounted on the time display section and having an hour hand rotating shaft disposed at a position different from the center position of the time display section;

a minute hand being mounted on the time display section and having a minute hand rotating shaft disposed at a position different from the center position of the time display section and concentric with the hour hand rotating shaft;

a pointer being mounted at a position eccentric from the center of the time display section and different from the hour hand rotating shaft and minute hand rotating shaft on the time display section and having a pointer rotating shaft, a dimension A from the pointer rotating shaft to a tip of the pointer being greater than a dimension B from the minute hand rotating shaft to a tip of the minute hand, and the pointer rotating shaft being disposed at a position away from the hour hand rotating shaft by a distance less than the dimension A and greater than the dimension B;

a movement being configured to drive the hour hand, the minute hand, and the pointer; and

a seconds hand that is being mounted on the time display section and has having a seconds hand rotating shaft at a position different from the pointer rotating shaft, wherein a dimension C from the seconds hand rotating shaft to the a tip of the seconds hand [[is]] being less than the dimension A, and the seconds hand rotating shaft [[is]] being disposed at a position away from the pointer rotating shaft by a distance greater than the dimension C and less than the dimension A.

6. (Previously Presented) The timepiece according to claim 5, wherein the pointer rotating shaft is disposed at a position eccentric from the center of the time display section in a 12:00 direction,

the hour hand rotating shaft and the minute hand rotating shaft are disposed at a position eccentric from the center of the time display section in a 6:00 direction, and

the seconds hand rotating shaft is disposed at a position eccentric from the center of the time display section in a 10:00 direction.

7. (Currently Amended) The timepiece according to claim 6, further comprising, a second pointer that is disposed on the time display section and has a second pointer rotating shaft at a position different from said the pointer rotating shaft, wherein a dimension D from the second pointer rotating shaft to the a tip of the second pointer is less than the dimension A, and the second pointer rotating shaft is disposed at a position away from the pointer rotating shaft by a distance less than the dimension A, wherein

the second pointer rotating shaft is disposed at a position eccentric from the center of the time display section about in a 2:00 direction.

8. (Original) The timepiece according to claim 7, wherein the second pointer is configured to be capable of rotating only within a specific angular range, and

the second pointer rotating shaft is disposed at a position away from the pointer rotating shaft by a distance less than the dimension D.

9. (Original) The timepiece according to claim 8, further comprising,

a case to accommodate the dial, the hour hand, the minute hand, the pointer, and the movement, and

a wrist mounting strap connected to the case.

10. (Currently Amended) The A timepiece according to claim 1, further comprising[[,]]:

a dial having a dial cover and a time display section on an inner peripheral side thereof;

an hour hand being mounted on the time display section and having an hour hand rotating shaft disposed at a position different from the center position of the time display section;

a minute hand being mounted on the time display section and having a minute hand rotating shaft disposed at a position different from the center position of the time display section and concentric with the hour hand rotating shaft;

a pointer being mounted at a position eccentric from the center of the time display section and different from the hour hand rotating shaft and minute hand rotating shaft on the time display section and having a pointer rotating shaft, a dimension A from the pointer rotating shaft to a tip of the pointer being greater than a dimension B from the minute hand rotating shaft to a tip of the minute hand, and the pointer rotating shaft being disposed at a position away from the hour hand rotating shaft by a distance less than the dimension A and greater than the dimension B; and

a movement being configured to drive the hour hand, the minute hand, and the pointer

a second pointer that is being mounted on the time display section and has having a second pointer rotating shaft at a position different from the pointer rotating shaft, wherein a dimension D from the second pointer rotating shaft to the a tip of the second pointer [[is]] being less than the dimension A, and the second pointer rotating shaft [[is]] being disposed at a position away from the pointer rotating shaft by a distance less than the dimension A.

## 11. (Currently Amended) A timepiece comprising:

a dial having a dial cover and a time display section on an inner peripheral side thereof;

an hour hand being mounted on the time display section and having an hour hand rotating shaft disposed at a position different from the center position of the time display section;

a minute hand being mounted on the time display section and having a minute hand rotating shaft disposed at a position different from the center position of the time display section;

a first pointer being mounted on the time display section and having a first pointer rotating shaft arranged to be eccentric from the center of the time display section and arranged in a different location from the minute hand rotating shaft and the hour hand rotating shaft on the time display section, a dimension A from the first pointer rotating shaft to a tip of the first pointer being greater than a dimension B from the minute hand rotating shaft to the a tip of the minute hand, and the first pointer rotating shaft being disposed at a position away from the hour hand rotating shaft by a distance less than the dimension A and greater than the dimension B;

a second pointer being mounted on the time display section and having a second pointer rotating shaft arranged eccentric from the center of the time display section and different from the first pointer rotating shaft, the second pointer being configured to be capable of rotating only within a specific angular range, a dimension D from the second pointer rotating shaft to a tip of the second pointer being shorter than the dimension A, and the second pointer rotating shaft being disposed at a position away from the pointer rotating shaft by a distance less than the dimension D; and

a movement being configured to drive the hour hand, the minute hand, the first pointer, and the second pointer.

12. (Original) The timepiece according to claim 10, wherein

the second pointer rotating shaft is disposed at a position eccentric from the center of the time display section about in a 2:00 direction,

the pointer rotating shaft is disposed at a position eccentric from the center of the time display section in a 12:00 direction, and

the hour hand rotating shaft and the minute hand rotating shaft are disposed at a position eccentric from the center of the time display section in a 6:00 direction.

13. (Original) The timepiece according to claim 12, further comprising, a case to accommodate the dial, the hour hand, the minute hand, the pointer, and the movement, and

a wrist mounting strap connected to the case.

- 14. (Previously Presented) The timepiece according to claim 10, wherein the pointer is a seconds chronograph hand, and the second pointer is a minute chronograph hand.
  - 15. (Original) The timepiece according to claim 14, further comprising, a date display section to display the date on the dial.
- 16. (Original) The timepiece according to claim 15, further comprising, a case to accommodate the dial, the hour hand, the minute hand, the pointer, and the movement, and

a wrist mounting strap connected to the case.

- 17. (Previously Presented) The timepiece according to claim 16, wherein the dial has seconds chronograph graduations and minute chronograph graduations.
- 18.-20. (Cancelled).